

MSDS No. 115

Tire Mounting Lube

revision date: 3/20/2006

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Stop spill at the source. Dike area & Contain. Clean up remainder with absorbent materials. Mop up & dispose of.

Waste Disposal Method: Recycle or dispose of observing local, state & Federal health, safety & pollution laws. If questions exist, contact the appropriate agencies.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Section 7 - Handling and Storage

Handling Precautions: Use safe practices when handling all chemical products.

Storage Requirements: Use safe storage practices.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls: General ventilation should be sufficient

Skin Protections: If irritation exists, wear clothing and gloves to protect from skin contact.

Respiratory Protection: None should be needed, but if signs of chemical exposure are observed, wear a NIOSH approved respirator.

Protective Clothing/Equipment: Wear chemically protective gloves to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Physical State: Liquid

Appearance and Odor: Amber liquid, with a soapy odor

Vapor Pressure: N/A

Vapor Density (Air=1): N/A

Specific Gravity (H₂O=1, at 4 °C): 1.03

Boiling Range: 127 C/ 260 F

Total VOC's: N/A

Hazardous Air Pollutants (HAPS): N/A

Percentage Volatile by Volume: N/A

Solubility in Water: Complete

Section 10 - Stability and Reactivity

Stability: Tire Mounting Lube is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: No known.

Conditions to Avoid: No Known.

Hazardous Decomposition Products: Thermal oxidative decomposition of Tire Mounting Lube can produce no known.

Section 11- Toxicological Information

No Toxicological information exists on this product.

Section 12 - Ecological Information

No Ecological information exists on this products. However use safe practices when disposing to avoid any adverse environmental effects.

Section 13 - Disposal Considerations

Disposal: Any disposal practice must be in compliance with local, state, and federal laws and regulations. Do not dump into sewer, on the ground or into any body of water.

Section 14 - Transport Information

DOT Transportation Data (49 CFR 172.101):

Non hazardous according to DOT guidelines.

revision date: 3/20/2006

Tire Mounting Lube

MSDS No. 115

Section 15 - Regulatory Information

All ingredients non hazardous and non regulated.

Section 16 - Other Information

Prepared By: TLC/ THI
Revision Notes: Updates

Disclaimer: The information above is believed to be accurate and represents the best information currently available to the Manufacturer and MSDS developer. However, we make no warranty of merchantability or any other warrant, express or implied, with respect to such information, and we assume no liability resulting from its use. User should make their own investigation to determine the suitability of the information for their particular purposes. In no way shall the Manufacturer or MSDS developer be liable for any claims, losses, or damage of any third party or for lost profits or any special, indirect, incidental consequential or exemplary damages, howsoever arising, even if the Manufacturer or MSDS developer has been advised of the possibility of such damages.